









F.A.B.

- Pure aluminum housing, better heat-sink.
- Plated and Satin finish, special out-looking.
- Outstanding dimming compatibility, matching the popular dimmers with leading edge, trailing edge and universal edge in Australia market.
- High-efficiency SMD LED chips.
- PC diffuser with soft-lighting, eyes-protection.
- High-efficiency LED chips.
- Cutout 2.5/3/4/6/8 inch are available.
- Up to 40,000 hrs life span.
- SAA/IC-F certificate passed.
- With 1.2m cable and plug

 240VAC	 11W	 120°	 Dimmable
CRI >80	 Flex&Plug	 ø92mm	



FLY series

11W
White / Silver Housing

MODEL NO.	Cutout	Housing	CCT	Watt	Voltage	Frequency	Lumen	CRI	Beam Angle	Packing
OM-DLR92W-11W-DL	ø 92mm	White	5000K	11W	220-240V~	50/60Hz	800lm	>80	120°	24pcs/ctn
OM-DLR92W-11W-WW	ø 92mm	White	3000K	11W	220-240V~	50/60Hz	750lm	>80	120°	24pcs/ctn
OM-DLR92S-11W-DL	ø 92mm	Silver	5000K	11W	220-240V~	50/60Hz	800lm	>80	120°	24pcs/ctn
OM-DLR92S-11W-WW	ø 92mm	Silver	3000K	11W	220-240V~	50/60Hz	750lm	>80	120°	24pcs/ctn

