

17 Lacey St  
 Croydon Vic 3136  
 Tel:1300 333 001 Fax:1300 333 002  
 E-mail:sales@omni-au.com

## Data Sheet



Model No	LP660-40W-DL/WH	LP312-40W-DL/WH	LP312-40W-CW/WH	LP312-40W-CCT/WH
Body Material	Aluminium	Aluminium	Aluminium	Aluminium
Diffuser	PC	PC	PC	PC
Lens Finish	Frost	Frost	Frost	Frost
Frame Colour	White	White	White	White
Colour Temp	6500K	6500K	4000K	2800K-6500K
Voltage	240V	240V	240V	240V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Wattage	40W	40W	40W	40W
Lumen	3600lm	3600lm	3400lm	3000lm-3400lm
PF	>0.9	>0.9	>0.9	>0.9
CRI	>80	>80	>80	>80
IP Rating	IP20	IP20	IP20	IP20
Driver	External	External	External	External
Power Cable	1.2m Flex&Plug	1.2m Flex&Plug	1.2m Flex&Plug	1.2m Flex&Plug
Dimmable	No	No	No	Yes
Life Time	30000 HRS	30000 HRS	30000 HRS	30000 HRS
LED Chip	Epistar 4014	Epistar 4014	Epistar 4014	Epistar 4014
Warranty	3 Years	3 Years	3 Years	3 Years
Installation	Surface Mounting	Surface Mounting	Surface Mounting	Surface Mounting
	Recessing	Recessing	Recessing	Recessing
	Suspending	Suspending	Suspending	Suspending
Size (mm)	595*595*10.5	295*1195*10.5	295*1195*10.5	295*1195*10.5
Packing	4 pcs /Carton	4 pcs /Carton	4 pcs /Carton	4 pcs /Carton

Accessories	LP660-FRSM	Surface mounting frame for LP660-40W
	LP312-FRSM	Surface mounting frame for LP312-40W
	LPA600	Suspending Kit for LP312-40W and LP660-40W