




Omni Electrical and Lighting Australia

17 Lacey St
 Croydon Vic 3136
 Tel:1300 333 001 Fax:1300 333 002
 E-mail:sales@omni-au.com

Data Sheet

OMNI



| Model No | LFLD-50WDL | LFLD-100WDL | LFLD-200WDL |
|---------------|------------------|------------------|------------------|
| Body Colour | Black | Black | Black |
| Body Material | Aluminium | Aluminium | Aluminium |
| Diffuser | Glass | Glass | Glass |
| Colour Temp | 6500K | 6500K | 6500K |
| Voltage | 240V | 240V | 240V |
| Frequency | 50/60Hz | 50/60Hz | 50/60Hz |
| Wattage | 50W | 100W | 200W |
| Beam Angle | 100° | 100° | 100° |
| Lumen | 5000lm | 10000lm | 20000lm |
| PF | >0.9 | >0.9 | >0.9 |
| CRI | >80 | >80 | >80 |
| Dimmable | No | No | No |
| IP Rating | IP65 | IP65 | IP65 |
| Life Time | 40000 HRS | 40000 HRS | 40000 HRS |
| LED Chip | Bridgelux 3030 | Bridgelux 3030 | Bridgelux 3030 |
| Driver | Omni | Omni | Meanwell |
| Power Cable | 1.2m Flex&Plug | 1.2m Flex&Plug | 1.2m Flex&Plug |
| Installation | Surface mounting | Surface mounting | Surface mounting |
| Warranty | 3 Years | 3 Years | 3 Years |
| Size (mm) | 220*282*113 | 387*340*257 | 510*420*270 |
| Net Weight | 2.5 kgs | 5.0 kgs | 8.2 kgs |
| Packing | 4 pcs /Carton | 1 pcs /Carton | 1 pcs /Carton |

