



Omni Electrical and Lighting Australia

17 Lacey St
 Croydon Vic 3136
 Tel:1300 333 001 Fax:1300 333 002
 E-mail:sales@omni-au.com

Data Sheet



Model No	LVPS-12W-WW/WH	LVPS-12W-CW/WH	LVPS-12W-DL/WH
Body Colour	White	White	White
Body Material	Aluminium	Aluminium	Aluminium
Diffuser	PC	PC	PC
Colour Temp	3000K	4000K	5000K
Voltage	240V	240V	240V
Frequency	50/60Hz	50/60Hz	50/60Hz
Wattage	12W	12W	12W
Beam Angle	60°	60°	60°
Gimballed Head	Yes	Yes	Yes
Lumen	900lm	950lm	1000lm
PF	>0.9	>0.9	>0.9
CRI	>80	>80	>80
Dimmable	Yes	Yes	Yes
IP Rating	IP20	IP20	IP20
Life Time	40000 HRS	40000 HRS	40000 HRS
LED Chip	Lextar 2835	Lextar 2835	Lextar 2835
Driver	External	External	External
Power Cable	1.2m Flex&Plug	1.2m Flex&Plug	1.2m Flex&Plug
Installation	Recessed	Recessed	Recessed
Cut out(mm)	90mm	90mm	90mm
Rating	IC-F	IC-F	IC-F
Warranty	5 Years	5 Years	5 Years
Size (mm)	110*48	110*48	110*48
Packing	24 pcs /Carton	24 pcs /Carton	24 pcs /Carton

Note: Warranty will be voided if the power lead removed