




Omni Electrical and Lighting Australia

17 Lacey St
 Croydon Vic 3136
 Tel:1300 333 001 Fax:1300 333 002
 E-mail:sales@omni-au.com

Data Sheet

OMNI



OMNI



OMNI



Model No	LFLD-20WDL	LFLD-50WDL	LFLD-100WDL	LFLD-200WDL
Body Colour	Black	Black	Black	Black
Body Material	Aluminium	Aluminium	Aluminium	Aluminium
Diffuser	Glass	Glass	Glass	Glass
Colour Temp	6500K	6500K	6500K	6500K
Voltage	240V	240V	240V	240V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Wattage	20W	50W	100W	200W
Beam Angle	100°	100°	100°	100°
Lumen	2000lm	5000lm	10000lm	20000lm
PF	>0.9	>0.9	>0.9	>0.9
CRI	>80	>80	>80	>80
Dimmable	No	No	No	No
IP Rating	IP65	IP65	IP65	IP65
Life Time	40000 HRS	40000 HRS	40000 HRS	40000 HRS
LED Chip	Bridgelux 3030	Bridgelux 3030	Bridgelux 3030	Bridgelux 3030
Driver	Omni	Omni	Omni	Meanwell
Power Cable	1.2m Flex&Plug	1.2m Flex&Plug	1.2m Flex&Plug	1.2m Flex&Plug
Installation	Surface mounting	Surface mounting	Surface mounting	Surface mounting
Warranty	3 Years	3 Years	3 Years	3 Years
Size (mm)	165*150*58	220*282*113	387*340*257	510*420*270
Net Weight	1.1 kgs	2.5 kgs	5.0 kgs	8.2 kgs
Packing	6 pcs /Carton	4 pcs /Carton	1 pcs /Carton	1 pcs /Carton