Omni Electrical and Lighting Australia

17 Lacey St
Croydon Vic 3136
Tel:1300 333 001 Fax:1300 333 002
E-mail:sales@omni-au.com

Data Sheet

Model No	LLW-18W-CW	LLW-18W-DL	LLW-36W-CW	LLW-36W-DL	LLW-45W-CW	LLW-45W-DL
Body Material	PC	PC	PC	PC	PC	PC
Diffuser	PC	PC	PC	PC	PC	PC
Lens Finish	Frost	Frost	Frost	Frost	Frost	Frost
Colour Temp	4000K	5000K	4000K	5000K	4000K	5000K
Voltage	240V	240V	240V	240V	240V	240V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Wattage	18W	18W	36W	36W	45W	45W
Beam Angle	120°	120°	120°	120°	120°	120°
Lumen	1500lm	1600lm	3100lm	3200lm	3900lm	4000lm
PF	>0.9	>0.9	>0.9	>0.9	>0.9	>0.9
CRI	>80	>80	>80	>80	>80	>80
IP Rating	IP65	IP65	IP65	IP65	IP65	IP65
Driver	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Power Cable	0.8m Flex	0.8m Flex	0.8m Flex	0.8m Flex	0.8m Flex	0.8m Flex
Dimmable	No	No	No	No	No	No
Life Time	30000 HRS	30000 HRS	30000 HRS	30000 HRS	30000 HRS	30000 HRS
LED Chip	EVERLIGHT 2835	EVERLIGHT 2835	EVERLIGHT 2835	EVERLIGHT 2835	EVERLIGHT 2835	EVERLIGHT 2835
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years
Installation	Surface Mounting/Suspending	Surface Mounting/Suspending	Surface Mounting/Suspending	Surface Mounting/Suspending	Surface Mounting/Suspending	Surface Mounting/Suspending
Size (mm)	600*60*35	600*60*35	1200*60*35	1200*60*35	1500*60*35	1500*60*35
Packing	20 pcs /Carton	20 pcs /Carton	20 pcs /Carton	20 pcs /Carton	20 pcs /Carton	20 pcs /Carton