



Omni Electrical and Lighting Australia

17 Lacey St
 Croydon Vic 3136
 Tel:1300 333 001 Fax:1300 333 002
 E-mail:sales@omni-au.com

Data Sheet



Model No	LSPD-100W-DL	LSPD-150W-DL	LSPD-200W-DL
Body Colour	Black	Black	Black
Body Material	Aluminium	Aluminium	Aluminium
Diffuser	Glass	Glass	Glass
Colour Temp	5000K	5000K	5000K
Voltage	AC100-277V	AC100-277V	AC100-277V
Frequency	50/60Hz	50/60Hz	50/60Hz
Wattage	100W	150W	200w
Beam Angle	120°	120°	120°
Lumen	15000lm	22500lm	30000lm
PF	>0.9	>0.9	>0.9
CRI	>80	>80	>80
Dimmable	YES PWM/1-10V	YES PWM/1-10V	YES PWM/1-10V
IP Rating	IP65	IP65	IP65
Life Time	50000 HRS	50000 HRS	50000 HRS
LED Chip	CREE SMD2835	CREE SMD2835	CREE SMD2835
Power Cable	2m Flex&Plug	2m Flex&Plug	2m Flex&Plug
Installation	Suspending / Surface mounting	Suspending / Surface mounting	Suspending / Surface mounting
Warranty	5 Years	5 Years	5 Years
Size(D/H-mm)	226*152	275*152	275*152
Net Weight	2.3kgs	3.0 kgs	3.0kgs
Packing	1 pcs /Carton	1 pcs /Carton	1 pcs /Carton

Accessory:

60 degree Aluminium Dome
 Surface Mounting Bracket